







8OLF D 5LVWD /HNLpD ' %DU 7HO
 æLUR 5D XQ &.% %DQND
 3LE 3'9

(PDLO KRQHO HOHFWRQLF#JPDLO F
 LQIR#KRQHO HOHFWRQLF FRP
 :HEZZ KRQHO HOHFWRQLF FRP

MODEL	SLIKA	KARAKTERISTIKE	CIJENA
Analoge Color CCTV Camere			
<p>ALS-C74DV3/2</p> 		<p>Outdoor IR dome DV3/2 (Metal), IP66, CMOS 1099; 960H; 800TVL; With ICR, no OSD, with ICR, 3.6mm lens, 23pcs φ5mm IR LED, IR range 20m, DC12V, PAL</p>	<p>Board Lens: 3.6mm Horizontal Angle of View: 78° </p>
<p>ALS-C74Q1</p> 		<p>IR bullet Q1 (Metal), IP66, 3.6mm, CMOS 1099; 960H; 800TVL; With ICR, no OSD, with ICR, 3.6mm lens, 23pcs φ5mm IR LED, IR range 20m, DC12V, PAL</p>	<p>Board Lens: 3.6mm Horizontal Angle of View: 78° </p>
<p>ALS-C80Q3</p> 		<p>IR bullet Q1 (Metal), IP66 1/3" Sony IMX225+ NVP2431H, 1000TVL (720P), with ICR, 3.6mm lens, 23pcs φ5mm IR LED, IR range 20m, DC12V, PAL,</p>	<p>Board Lens: 3.6mm Horizontal Angle of View: 78° </p>
<p>ALS-9602DV21A</p> 		<p>Outdoor IR dome with Varifocal lens:IP66, Sony Effio E (4140) + 811/810AK CCD, 700TVL, 36pcs φ5mm IR leds, IR range 35-40m, 2.8-12mm Manual VF lens, UTC control OSD, UTC controller optional, 2DNR, ATR DC12V</p>	<p>Varifocal Lens 2.8-12mm IR - Corrected Horiz. Angle of view: 99°-24° </p>
<p>ADV-950</p> 	   	<p>1/3" CCD WDR, DNR, Color, Armour Dome OSD Camera SONY-Effio DSP CXG4140GG + SONY CCD EX view HAD II - ICX673AKA</p> <p>Power: 65mA IP-65 Outdoor Armour Dome:(Aluminium Vandal Resistant) 140(Ø) x 90(H)mm - 70g Housing: Beige color</p> <p>700TVL OSD 2.8~10mm 0.03 Lux WDR DNR</p>	<p>Lens 2.8-12mm/F1.6 Horiz. Angle of view: 99°-27°  <p>EXview HAD CCD II SONY - ICX673AKA</p> </p>
<p>ADB-150</p>		<p>Metal Dome camera Bracket for ARMOUR Dome Housing - (beige) SUITABLE FOR Armour Dome Cameras: ADV-950</p>	<p>9,00</p>
<p>CAM-9702IV6C</p> 		<p>Waterproof IR camera IV6C IP66, Sony Effio A (4151) + 811/810AK CCD,700TVL 42pcs φ5mm IR leds,35-40m IR distance, with Video test output, LED level adjusting 2.8-12mm Manual VF lens, DC12V</p>	<p>Varifocal Lens 2.8-12mm IR - Corrected Horiz. Angle of view: 99°-24° </p>
<p>CAM-9702IV7C</p> 		<p>Waterproof IR camera IV7C IP66, Sony Effio A (4151) + 811/810AK CCD, 700TVL, 72pcs φ5mm IR leds, 40-45m IR distance, with Video test output, LED level adjusting 2.8-12mm manual VF lens optional OSD, 3DNR, ATR-EX2 (DWDR), Sense-UP, Defog, DC12V</p>	<p>Varifocal Lens 2.8-12mm IR - Corrected Horiz. Angle of view: 99°-24° </p>
<p>CAM-9702IV7C</p> 		<p>Sony Effio A (4151) + 811/810AK CCD, 700TVL, 72pcs φ5mm IR leds, 40-45m IR distance, with Video test output, LED level adjusting 6-22mm manual VF lens optional OSD, 3DNR, ATR-EX2 (DWDR), Sense-UP, Defog, DC12V</p>	<p>Varifocal Lens 6-22mm IR - Corrected </p>

<p>PIR-500A Videosec</p>	 	<p>1/3" SONY PIR Case Hidden CCD WDR COLOR 3-Axis OSD Camera. DSP NEXTchip2090E + SONY CCD HAD II - ICX811, 700TVL</p> <p>Power: 12VDC- 80mA Size:70(W)x48(D)x120(H)mm</p> <p>650TVL OSD 3.7mm 0.05 Lux WDR DNR</p>	<p>Pinhole Lens 3.7mm/F2.0 IR - Corrected Horiz. Angle of view: 75°</p> <p>Super HAD CCD II SONY - ICX 811</p>	<p>49,40</p>
--	---	---	--	---------------------

DAHUA Stand Alone DVRs H-264



<p>DVR-2116C alhua</p>	 	<p>Real Time/D1 - H.264 - PENTAPLEX DVR DVR: 25fps/2CIF-12fps/D1/CH, LAN VGA-1080p, 1 sata HDDs, 2xUSB HDD NOT included</p> <p>CIF 25fps D1 12fps 1xHDD HDMI 1080p HDMI / VGA</p> <p>D1: 704x576 / CIF:352x288 Real time recording</p>	<p>16Ch DVR 16x Video IN</p>	<p>117,0</p>
<p>iDVR5104H-F alhua</p>		<ul style="list-style-type: none"> • Support 1080P HD preview; • Support 960H + CIF real-time encoding • Support 4/8/16 channel synchronous playback; • Support HDMI / VGA / BNC sync output display; • Support 485 and 1 channel audio input, 1 channel audio output 	<p>960H - 4Ch DVR 4x Video IN IP Camera IN - Max. 2Ch 1x Audio IN RS485, LAN 2xUSB</p>	<p>95,0</p>
<p>iDVR5108H-F alhua</p>	 	<ul style="list-style-type: none"> • Support Dahua DDNS.; • Support multi-screen preview (zero channel coding); • Standard 1U chassis supports a SATA hard drive, the largest hard drives 	<p>960H - 8Ch DVR 8x Video IN IP Camera IN - Max. 2Ch 1x Audio IN RS485, LAN 2xUSB</p>	<p>132,0</p>
<p>iDVR5116H-F alhua</p>	 	<ul style="list-style-type: none"> • Support 4T face detection and face video playback • Support for hard disk repair daemon 	<p>960H - 16Ch DVR 16 x Video IN IP Camera IN - Max. 2Ch 1x Audio IN RS485, LAN 2xUSB</p>	<p>192,0</p>






























AHD Kit/ 720P (Analog HD Kit: AHD DVR + AHD Camera + BNC/DC Cable + Power Adapter)






<p>AHD KIT CAM-KAE4102</p>		<p>* AHD DVR, 4CH 720P @ 25/30fps * Input:4CH 720P AHD or 2CH AHD+2CH 960H * 4CH 720P realtime playback * Support 1 SATA HDD up to 4TB * HDD not included in kit</p>	<p>CAM-AVR204</p>	
<p>AHD KIT CAM-KAE4102</p>		<p>* AHD Camera, 1/2.8" Sony IMX238 + NVP2431H * 1.3 Megapixel, 720P@25/30fps, Low Lux * 23pcs φ5mm IR LED, IR range 20m, 3.6mm, OSD</p>	<p>CAM-MA105W46</p>	
<p>CAMSTAR</p>		<p>* AHD Camera, 1/2.8" Sony IMX238 + NVP2431H * 1.3 Megapixel, 720P@25/30fps, Low Lux * 23pcs φ5mm IR LED, IR range 20m, 3.6mm, OSD</p>	<p>CAM-MA105DV3/2</p>	<p>320,0</p>
<p>CAMSTAR</p>		<p>CB-BD20, 20meter long BNC/DC cable</p>	<p>CB-BD20</p>	
		<p>DC12V, 5A Power adapter, AC100-240V power input * European plug for PAL system, American plug for NTSC system</p>	<p>DC12V/5A + 1 in 4 out Power Cord</p>	

HD CVI Camera (Composite Video Interface)


720p (1Mp) HDCVI Cameras (High Definition Composite Video Interface over coaxial cable max. 500m- 20.5MHz - 41 Mbit/s)






















<p>HAC-HDW1100RP alhua</p>	 <p>HDCVI</p>	<p>1/2.9" 1Megapixel CMOS 25/30fps@720P High speed, long distance real-time transmission Day/Night(ICR), AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs length 20m, Smart IR DC12V</p>	<p>Mega Lens: 3.6mm/1.8 Horizontal Angle of View: 78°</p>	<p>39,0</p>
<p>ALS-MC101DV3/2 CAMSTAR</p>	 <p>HDCVI</p>	<p>Outdoor IR dome DV3/2 (Metal), IP66, 1/2.9" Pixelplus CMOS sensor, 1 Megapixel, 720P@25/30fps, with ICR, 3.6mm lens, 23pcs φ5mm IR LED, IR range 20m, DC12V, PAL</p>	<p>Mega Lens: 3.6mm/1.8 Horizontal Angle of View: 78°</p> <p>100% METAL</p>	<p>45,0</p>

ALS-MC101DV6/2 	 HDCVI	Outdoor IR dome DV6/2 (Metal), IP66, 1/2.9" Pixelplus CMOS sensor, 1 Megapixel, 720P@25/30fps , with ICR, 2.8-12mm manual VF lens , 36pcs ϕ 5mm IR LED, IR range 30-35m, DC12V, PAL	Varifocal Lens 2.8-12mm/F1.4 Horiz. Angle of view: 99°~24° 	63,0
HAC-HFW1100R 	 HDCVI	1/2.9" 1Megapixel CMOS 25/30fps@ 720P High speed, long distance real-time transmission Day/Night(ICR), AWB, AGC, BLC, 2D-DNR 3.6mm fixed lens Max. IR LEDs length 20m, Smart IR IP66, DC12V	Mega Lens: 3.6mm/1.8 Horizontal Angle of View: 78°	39,0
ALS-MC101Q3 	 HDCVI	IR bullet Q3 (Metal), IP66, 1/2.9" Pixelplus CMOS sensor, 1 Megapixel, 720P@25/30fps, with ICR, 3.6mm lens , 23pcs ϕ 5mm IR LED, IR range 20m, DC12V, PAL	Mega Lens: 3.6mm/1.8 Horizontal Angle of View: 78° 	47,0
HAC-HFW1100S 	 HDCVI	1/2.9" 1 Megapixel CMOS 25/30fps@720P High speed, long distance real-time transmission Day/Night(ICR), AWB, AGC, BLC, 2D-DNR 3.6mm optional Max. IR LEDs length 30m, Smart IR IP67, DC12V	Mega Lens: 3.6mm/1.8 Horizontal Angle of View: 78° 	54,0
CAM-MC101Q2 	 HDCVI	IR bullet Q3 (Metal), IP66, 1/2.9" CMOS sensor PV1100K, 1 Megapixel, 720P@25/30fps , with ICR, 2.8-12mm manual VF lens , 36pcs ϕ 5mm IR LED, IR range 30-35m, DC12V, PAL,	Varifocal Lens 2.8-12mm/F1.4 Horiz. Angle of view: 99°~24° 	60,0
ALS-MC101IV6C 	 HDCVI	IR bullet IV6C (Metal), IP66, 1/2.9" Pixelplus CMOS sensor, 1 Megapixel, 720P@25/30fps , with ICR, 2.8-12mm manual VF lens , ϕ 5mm IR LED, IR range 35-40m, PAL	Varifocal Lens 2.8-12mm/F1.4 Horiz. Angle of view: 99°~24° 	87,0
1080p (2Mp) HDCVI Cameras (High Definition Composite Video Interface over coaxial cable max. 250m- 41MHz - 82 Mbit/s)				
ALS-MC202DV3/2(3.6) 	 HDCVI	 Outdoor IR dome DV3/2 (Metal), IP66, 1/2.7" ZA20S10 Sensor 2 Megapixel, 1080P@25/30fps , with ICR, 3.6mm lens, 23pcs ϕ 5mm IR LED, IR range 20m, DC12V, PAL 	Mega Lens: 3.6mm/1.8 Horizontal Angle of View: 78°	61,0
ALS-MC202DV6/2 	 HDCVI	 Outdoor IR dome DV6/2 (Metal), IP66, 2.8-12mm VF lens, 1/2.7" ZA20S10 Sensor 2 Megapixel, 1080P@25/30fps , with ICR, 36pcs ϕ 5mm IR LED, IR range 30-35m, 2.8-12mm manual VF lens, DC12V, PAL 	Varifocal Lens 2.8-12mm/F1.4 Horiz. Angle of view: 99°~24°	81,0
CAM-MC205DV6/2 	 HDCVI	 Outdoor IR dome DV6/2 (Metal), IP66, 1/2.8" Sony IMX322 + Eyenix EN773E, 2 Megapixel, 1080P@25/30fps , with ICR, 2.8-12mm Motorized lens , 36pcs ϕ 5mm IR LED, IR range 30-35m, DC12V, PAL 	Motorized Varifocal Motorized Lens Auto Iris-ICR Filter Motorized 2.8-12mm with AUTO FOCUS	104,0

<p>ALS-MC202Q3</p> <p>CAMSTAR</p>	 <p>HDCVI</p>	<p>IR bullet Q3 (Metal), IP66, 1/2.7" ZA20S10 Sensor 2 Megapixel, 1080P @25/30fps, with ICR, 3.6mm lens, 23pcs φ5mm IR LED, IR range 20m, DC12V, PAL</p> <p>FullHD 1920x1080</p> <p>100% METAL</p>	<p>Mega Lens: 3.6mm/1.8 Horizontal Angle of View: 78°</p>	<p>63,0</p>
<p>HAC-HFW2200S</p> <p>alhua</p>	 <p>HDCVI</p>	<p>1/3" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P High speed, long distance real-time transmission HD and standard definition switch. OSD Menu, control over coaxial cable>Day/Night(ICR), AWB, AGC, BLC, 3D-DNR, 3.6mm optional Max. IR LEDs length 20m, Smart IR IP66, DC12V</p> <p>FullHD 1920x1080</p> <p>100% METAL</p>	<p>Mega Lens: 3.6mm/1.8 Horizontal Angle of View: 78°</p>	<p>92,0</p>
<p>CAM-MC202Q2</p> <p>CAMSTAR</p>	 <p>HDCVI</p>	<p>IR bullet Q3 (Metal), IP66, 1/2.7" ZA20S10 Sensor, 2 Megapixel, 1080P @25/30fps, with ICR, 3.6mm optional φ5mm IR LED, range 30-35m, DC12V, PAL</p> <p>FullHD 1920x1080</p> <p>100% METAL</p>	<p>Varifocal Lens 2.8-12mm/F1.4 Horiz. Angle of view: 99°~24°</p>	<p>78,0</p>
<p>ALS-MC202IV6C</p> <p>CAMSTAR</p>	 <p>HDCVI</p>	<p>IR bullet IV6C (Metal), IP66, 2.8-12mm VF lens, 1/2.7" ZA20S10 Sensor * 2 Megapixel, 1080P @25/30fps, * with ICR, 42pcs φ5mm IR LED, IR range 35-40m, 2.8-12mm manual VF lens, DC12V, PAL</p> <p>FullHD 1920x1080</p> <p>100% METAL</p>	<p>Varifocal Lens 2.8-12mm/F1.4 Horiz. Angle of view: 99°~24°</p>	<p>103,0</p>
<p>HAC-HDBW2220R-Z</p> <p>alhua</p>	 <p>HDCVI</p>	<p>1/2.8" 2.4Megapixel CMOS 25/30@1080P, 25/30/50/60fps@720P High speed, long distance real-time transmission HD and standard definition switchable OSD Menu, control over coaxial cable Day/Night(ICR), AWB, AGC, BLC, 3D-DNR 2.7-12mm motorized lens Max. IR LEDs length 30m, Smart IR IP66, IK10, DC12V</p> <p>FullHD 1920x1080</p> <p>100% METAL</p>	<p>Motorized Varifocal Motorized Lens Auto Iris-ICR Filter Motorized 2.7-12mm with AUTO FOCUS</p>	<p>139,0</p>
<p>HAC-HFW2220RP-Z</p> <p>alhua</p>	 <p>HDCVI</p>	<p>1/2.8" 2.4Megapixel CMOS 25/30@1080P, 25/30/50/60fps@720P High speed, long distance real-time transmission HD and standard definition switchable OSD Menu, control over coaxial cable Day/Night(ICR), AWB, AGC, BLC, 3D-DNR 2.7-12mm motorized lens Max. IR LEDs length 30m, Smart IR IP66, DC12V</p> <p>FullHD 1920x1080</p> <p>100% METAL</p>	<p>Motorized Varifocal Motorized Lens Auto Iris-ICR Filter Motorized 2.7-12mm with AUTO FOCUS</p>	<p>139,0</p>
<p>SD59220I-HC</p> <p>alhua</p>	 <p>HDCVI</p>	<p>20xoptical zoom Max. 25/30fps@1080P(1920 x 1080) & 20/30/50/60fps@720P resolution DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 400°/s pan speed, 360° endless pan rotation Control over coaxial cable, long distance real-time transmission HD and SD switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in 2/1 alarm in/out Support intelligent 3D positioning with DH-SD protocol IR Distance up to 100m IP66, OSD</p> <p>FullHD 1920x1080</p>		<p>628,0</p>

HCVR-ovi

<p>HCVR-4104HS-S2</p> <p>alhua</p>		<p>Support HDCVI/Analog/IP Video input H.264 dual-stream video compression HCVR4104H-S2: All channel 720P recording HDMI/VGA simultaneous video output 4 channel synchronous playback, GRID interface & smart search Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc. ONVIF Version 2.4 conformance Support 1 SATA HDD up to 4TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)</p>	<p>80,0</p>
<p>HCVR-4108HS-S2</p> <p>alhua</p>	<p>Tribrid</p> <p>HDCVI</p>	<p>Support HDCVI/Analog/IP Video input H.264 dual-stream video compression HCVR4108H-S2: All channel 720P recording HDMI/VGA simultaneous video output 8 channel synchronous playback, GRID interface & smart search Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc. ONVIF Version 2.4 conformance Support 1 SATA HDD up to 4TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)</p>	<p>120,0</p>

<p>HCVR4108C-S2</p> 	 <p>Tribrid HDCVI</p>	<p>Support HDCVI/Analog/IP Video input H.264 dual-stream video compression HCVR4108-S2: All channel 720P recording HDMI/VGA simultaneous video output 8 channel synchronous playback, GRID interface & smart search Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc. ONVIF Version 2.4 conformance Support 1 SATA HDD up to 4TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)</p>	<p>113,0</p>	
<p>HCVR-5104C</p> 	 <p>HDCVI</p>	<p>H.264 Dual Stream Up to 4 x 1080p HD CVI Real-time preview CVI 4x HD 1080p / 12fps or 720p / 25fps recording 2 x IP camera 1080p / 12fps, 720p / 25fps USB and Ethernet connection, Suitable for browser and SmartPSS software VGA and HDMI video output, Max. 1 x 4TB HDD, S.M.A.R.T. HDD Diagnostic, Individual camera settings. Alarm, motion, and / or continuous shooting, Settings via mouse, or Web Client DMSS app to watch live, playback and receiving push notifications Email function with snapshots, Multi Playback and Backup Incl. 1TB HDD, Dimensions: 205 x 205 x 45 mm.</p>	<p>104,0</p>	
<p>HCVR-5108H</p> 	 <p>HDCVI</p>	<ul style="list-style-type: none"> • Up to 8 cameras with 1080p realtime preview • H.264 dual-stream video compression • HDMI / VGA simultaneous video output • 4 channel synchronous realtime playback, GRID interface & smart search • Support 1 SATA HDD up to 4TB, 2 USB2.0 • Multiple network monitoring: Web viewer, VMS & MMS • Version 2.24 Languages version, support 8CHx1080P@12fps,8CHx720P@25/30fps,not compatible with Dahua PSS 	<p>HDCVI DVR 8 Channel 720P Mini 1U</p>	<p>162,0</p>
<p>HCVR5104H-S2</p> 		<p>Support HDCVI/Analog/IP Video input H.264 dual-stream video compression HCVR5104H-S2: All channel 720P realtime or 1080P non-realtime recording HDMI/VGA simultaneous video output 4channel synchronous realtime playback, GRID interface & smart search Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc. NVIF Version 2.4 conformance Support 1 SATA HDD up to 4TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)</p>	<p>111,0</p>	
<p>HCVR5108H-S2</p> 	 <p>Tribrid HDCVI</p>	<p>Support HDCVI/Analog/IP Video input H.264 dual-stream video compression HCVR5108H-S2: All channel 720P realtime or 1080P non-realtime recording HDMI/VGA simultaneous video output 8channel synchronous realtime playback, GRID interface & smart search Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc. NVIF Version 2.4 conformance Support 1 SATA HDD up to 4TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)</p>	<p>174,0</p>	
<p>HCVR5116H-S2</p> 	<p>Tribrid HDCVI</p>	<p>Support HDCVI/Analog/IP Video input H.264 dual-stream video compression HCVR5116H-S2: All channel 720P realtime or 1080P non-realtime recording HDMI/VGA simultaneous video output 16channel synchronous realtime playback, GRID interface & smart search Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc. NVIF Version 2.4 conformance Support 1 SATA HDD up to 4TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)</p>	<p>294,0</p>	
<p>HCVR-5216A</p> 	 <p>HDCVI</p>	<p>16 Ch HDCVI Stand Alone Real Time DVR 2 sata HDDs, 2xUSB, HDMI-VGA out Recording: 720P (1280x720) (Max. 25/30fps)/Ch • All channel synchronous playback, GRID interface & smart search • OSD Menu, control over coaxial cable HDD NOT included</p>       	<p>HDCVI - DVR 16ch-(720p/200fps) 4x Audio IN 2 SATA Ports 12VDC OSD over COAX RS-485</p>	<p>331,0</p>
<p>HCVR-5216A-V2</p> 	 <p>Tribrid HDCVI</p>	<p>Support HDCVI/Analog/IP Video input Up to 16 cameras with 1080p realtime preview H.264 dual-stream video compression HCVR5204/5208/5216A-V2: All channel 720P realtime or 1080P non-realtime recording 16 channel synchronous realtime playback, GRID interface & smart search HDMI/VGA simultaneous video output. Support 2 SATA HDDs up to 8TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera ONVIF Version 2.3 conformance Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotech , and etc. Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)</p>	<p>348,5</p>	

<p>HCVR-5104HE</p>  <p>ahua TECHNOLOGY</p> <p>HDCVI</p>		<p>Support HDCVI/IP cameras input H.264 dual-stream video compression HCVR5104V2: All channel 720P realtime or 1080P non-realtime recording HDMI/VGA simultaneous video output 4channel synchronous realtime playback, GRID interface & smart search 3D intelligent positioning with Dahua PTZ dome camera Support 1 SATA HDD up to 4TB, 2 USB2.0 Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)</p>	<p>4ch-(1080p/50fps) 4x Audio IN 1 SATA Ports 4 Alarm Inputs RS-485</p>	<p>144,0</p>
IP Camere				
<p>HDBW-1000S</p>  <p>ahua TECHNOLOGY</p>		<p>1/4" 1Megapixel progressive scan CMOS H.264&MJPEG dual-stream encoding 25/30fps@720P(1280×720) DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens Max. IR LEDs Length 30m moke glass & transparent glass optional IP66, IK10, PoE</p>	<p>98,0</p>	
<p>HDW-4100S</p>  <p>ahua TECHNOLOGY</p>		<p>1/3" 1.3Megapixel progressive scan Aptina CMOS H.264&MJPEG dual-stream encoding Max 25/30fps@1.3M(1280×960) & 720P(1280×720) DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens Max. IR LEDs Length 20m IP66, PoE</p>	<p>164,0</p>	
<p>HFV-4200S</p>  <p>ahua TECHNOLOGY</p> <p>FULL HD 1920x1080</p> <p>ECO-SAVVY</p>		<p>1/2.8" 2Megapixel progressive scan Exmor CMOS H.264&MJPEG dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens (6mm,8mm optional) Max. IR LEDs Length 30m IP66, PoE</p>	<p>181,00</p>	
Dahua Stand Alone NVRs				
<p>NVR-4108H-P</p>  <p>ahua TECHNOLOGY</p>		<p>Up to 8channel IP camera input Max 80Mbps incoming bandwidth Up to 5Mp resolution preview&playback H.264/MJPEG dual codec decoding HDMI/VGA simultaneous video output All channel synchronous realtime playback, GRID interface Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc. ONVIF Version 2.4 conformance 3D intelligent positioning with Dahua PTZ camera Support 1 SATA HDD up to 4TB, 2 USB2.0 Support IPC UPnP, 4PoE ports Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS</p>	<p>185,00</p>	
<p>NVR-3216</p>  <p>ahua TECHNOLOGY</p>		<p>Up to 16 channel 1080P cameras realtime live view H.264/MJPEG dual codec decoding Max 120fps@1080p, 240fps@720p,480fps@D1 preview & recording HDMI / VGA simultaneous video output All channel synchronous realtime playback, GRID interface Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc. ONVIF Version 2.0 conformance 3D intelligent positioning with Dahua PTZ camera Support 2 SATA HDDs up to 8TB, 2 USB2.0 Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS</p>	<p>199,00</p>	
accessories				
<p>ZBL-RT3070-3</p>  <p>ahua TECHNOLOGY</p>		<p>WPA, WPA2, WEP Security Wireless 802.11b/g/n compatible Up to 300Mbps Data Speed 2.4GHz Frequency Band</p>	<p>Wi-Fi USB Dongle for Dahua DVRs & NVRs</p>	<p>19,00</p>
<p>UREĐAJ ZA OTKLANJANJE SMETNJI</p> 		<p>Video anti-interference device</p>	<p>13,00</p>	
<p>DC-DC CONVERTER</p> 		<p>DC-DC CONVERTER</p>	<p>11,00</p>	
<p>AC-DC CONVERTER</p> 		<p>AC-DC CONVERTER</p>	<p>11,00</p>	

AKTIVNI VIDEO BALUN (Receiver)		Active Video Balun	12,50
AKTIVNI VIDEO BALUN (Transmitter)		Active Video Balun	12,50
CAM-RU01		UTC Controller	8,00
PASIVNI VIDEO BALUN		Passive Video Balun	2,00
MICROFON-02		Mini CCTV Microphone For CCTV Cameras	5,00
MICROFON-04		Mini CCTV Microphone For CCTV Cameras	9,00
AM-02		EXTERNAL AUDIO MODULE built in DIY cable Audio output: 2Vp-p/50Ω/RCA Plug, Power Supply: 12VDC-20mA, nput: Electret Condenser Microphone -60dB, 50Hz-13KHz, S/N Ratio 40dB or more.	9,00
PDC-4	 1 To 4 Split Cable	DC Power split Cable with connectors size: Ø5.5*Ø2.1*10mm (to split from 1 adaptor to 4 CCTV Cameras)	2,00
PDC-8		Power Adapter DC Y Cable Pigtail 1 to 8 ,2.1mm,2.1mm	3,00
BNC-BNC (1M)		BNC Male Coax to BNC Male Coax:1M	1,50
RG+DC (20M)		Video,Power Cable:20M	8,00
RG59+2*0,75mm		95%CCA+2*0,75mm (305m)	152,50
RG59+2*0,75mm HALOGEN FREE		RG59 Cable :0.81mmCCA+3.66mmFPE+B.AL+95%CCA+6.1mm HALOGEN FREE (305m)	165,00
12V/1A		Power Adapter 12V/1A	5,00
RA-1300		Regulated AC/DC Switching Adaptor 230VAC/12VDC-1A (12W)	5,00
RA-2300		Regulated AC/DC Switching Adaptor 230VAC/12VDC-2A (24W)	7,00
12V/2A		Power Adapter 12V/2A	7,00
RA-2000		Regulated AC/DC Switching Adaptor 12VDC-2A (24W) (Wall Mount Style with LED Indicator) 1.5m DC Cable with connector size: Ø5.5*Ø2.1*10mm, with annular core and Ferrite Passive Low Pass Filter Input: 100-240VAC / Output: 12-13VDC - max 2000mA • Over Load Protection • Over Current Protection • Over Voltage Protection • Short Circuit Protection The power supply will be auto recovered when over current faults remove. The product to be dropped from 1 meter height to a concrete floor no breakage Certification: TUV-GE,UL,cUL,GS,BS,CB,EK,SA,CEC,FCC,PSE,S-MARK/REACH/EUP/MEPS, CCC approval, RoHS	8,00
12V/5A		Power Adapter 12V/5A - 60W	14,00
12V/10A		Power Adapter 12V/10A - 120W	20,00
12V/20A		Power Adapter 12V/20A - 240W	34,00

12V/10A/9S		Input: AC 100-240V Output: DC 12V 10A Channels: 9 CH	55,00
12V/20A/18S		Input: AC 100-240V Output: DC 12V 20A Channels: 18 CH	70,00
BNC NA ŠARAF		BNC connector for RG59, Cable, Free Welding	0,50
BNC NA LEMLJENJE		BNC connector for RG59, Cable, Welding	0,50
BNC NA KRIMPOVANJE		BNC Crimp Plug for RG59 Cable	0,50
BNC NA ŠARAF		BNC straight screw connector	0,40
BNC TWIST KONEKTOR		BNC Twist On Connectors For RG 59 Cable	0,50
ČINČ/BNC		BNC Male to RCA Female connector	0,50
BNC NASTAVAK		BNC Female to Female coupler connector	0,40
BNC T-KONEKTOR		T type ,bnc for connecting, 2 plugs:one male to double female	0,60
BNC/ČINČ		RCA Female to BNC Male connector	0,50
ČINČ KONEKTOR		RCA connector, free Welding	0,50
PMC		DC Power MALE Connector (size: Ø5.5*Ø2.1*10mm)	0,40
PFC		DC Power FEMALE Connector (size: Ø5.5*Ø2.1*10mm)	0,40

Cjenovnik video nadzora Jul 2015. sa uracunatim pdv-om.